

Cırcır Mekanizmalı Endüstriyel Tork Anahtarları

Industrial Torque Wrenches with Ratchet Mechanism



2 - 600 N.m



- › TS EN ISO 6789 standardına uygun $\pm 3\%$ hassasiyet
- › 2 – 600 N.m kapasitede farklı tork anahtarları
- › Endüstriyel uygulamalara uygun sağlam yapı
- › Sıkma - sökme işlerini kolaylaştıran mandallı cırcır
- › Yön seçimi cırcır üzerindeki mandal ile yapılır
- › Hızlı lokma değişimi sağlayan cırcır mekanizması
- › Hassas ve okunaklı mikrometre tip tork ayar skalası
- › Seri numaralı izlenebilir tork kalibrasyon sertifikası
- › DIN ISO 6789 & ASME B107.300-2010 kalite standardı
- › Türkiye’de servis, yedek parça ve kalibrasyon imkânı



- › Accuracy $\pm 3\%$ according to TS EN ISO 6789
- › Different torque wrenches in the range of 2 to 600 N.m
- › Suitable for heavy duty industrial applications
- › Robust ratchet mechanism for CW and CCW directions
- › Direction selection is applied from top of the ratchet
- › Ratchet mechanism providing rapid socket change
- › Precise, easy-to-read micrometer type torque setting scale
- › Ergonomic shape with non-slip knurled handle design
- › DIN ISO 6789 & ASME B107.300-2010 quality standard
- › Traceable calibration certificate for the clockwise direction

Parça Part	Tork Kapasitesi Torque Range		Kare Sürücü Square Drive	Cırcır Diş Ratchet Teeth	Ölçek Increment	Uzunluk Length	Ağırlık Weight
No.	N.m	Lb.ft - Lb.in	inch	#	N.m	mm	kg
TW-262-1FW*	2-10	22-84	1/4"	24T	0.1	281	0,60
TW-262-2FW*	4-20	40-172	1/4"	24T	0.1	329	0,65
TW-369-1FW	10-60	9.2-42.4	3/8"	32T	0.5	370	0,84
TW-369-2FW	20-100	16.6-71.9	3/8"	32T	0.5	433	1,0
TW-469-8FW	20-100	16.6-71.9	1/2"	32T	0.5	433	1,0
TW-469-1FW	40-200	33-144	1/2"	32T	1.0	530	1,65
TW-469-3FW	50-350	44-251	1/2"	32T	2.0	610	1,8
TW-469-5FW	60-420	52-302	1/2"	32T	2.0	610	1,8
TW-469-4FW	80-400	66-288	1/2"	32T	2.0	610	1,8
TW-669-1FW	100-600	92-424	3/4"	24T	5.0	1050	5,3

* Bu modeller plastik tutma koluna sahiptir. / These models have a plastic handle.

