

CTX Serisi Değişken Uçlu Tork Anahtarları

Interchangeable Adjustable Torque Wrenches

2,5 - 400 N.m



Wera
BE A TOOL REBEL



- › ISO 6789-1:2017-07 standardına uygun $\pm 3\%$ hassasiyet
 - › 2.5 – 400 N.m kapasitede farklı tork anahtarları
 - › Tork değeri kolay ayarlanır, birim skalası okunaklıdır
 - › Mikrometre tip paneli ile hasas ayar imkanı
 - › 9x12 ve 14x18 dikdörtgen girişli uçlarla kullanılır
 - › Açık ağız, yıldız, yarım yıldız ve cırcır uç takılabilir
 - › Cırcır uç takılarak lokmalı kullanıma uygun hale gelir
 - › Tutuşu kolaylaştıran kaymayan sağlam kabza
 - › Seri numaralı izlenebilir tork kalibrasyon sertifikası
 - › 1 yıl garantili, kalibrasyon belgesi, Alman Wera marka
- › Accuracy $\pm 3\%$ according to TS EN ISO 6789-1:2017-07
- › Different torque wrenches from 2.5 to 400 N.m
- › Micrometer type scale allows to easy adjust the torque
- › Used with rectangular input insert tools (9x12 and 14x18)
- › Open-end, ring-end & open-ring insert tool options
- › Sockets can be used with ratchet insert tool
- › Ergonomic shape with non-slip and comfortable handle
- › Traceable calibration certificate for the clockwise direction
- › 1 year warranty, calibration certificate, German Wera brand

Model Adı Model Name	Parça Part	Tork Kapasitesi Torque Range		Ölçek Increment	Uç Giriş Ölçüsü Insert Tool	Uzunluk Length
#	No.	N.m	lbf.ft	N.m	mm	mm
CT X1	05075651001	2,5-25	4-18	0,10	9x12	283
CT X2	05075652001	10-50	8-36	0,25	9x12	338
CT X3	05075653001	20-100	15-73	0,5	9x12	372
CT X4	05075654001	40-200	30-146	1,0	14x18	480
CT X5	05075655001	60-300	45-220	1,0	14x18	570
CT X6	05075656001	80-400	60-295	1,0	14x18	655



Uç Seçenekleri / Insert Tool Options

