

# VOLTA Dijital Kontrollü Akülü Tork Anahtarları

VOLTA Digital Controlled Battery Powered Torque Wrenches

torcUT

VT Series



- >  $\pm 5\%$  yüksek hassasiyetli torklama işlemi
  - > Fabrika çıkışlı seri numaralı kalibrasyon belgesi
  - > 160 - 4.000 N.m arası dört farklı model seçeneği
  - > Dijital tork ayar paneli ile hassas ve hatasız kullanım
  - > N.m ve Lbf.ft birimlerinde torklama imkânı
  - > Kömürsüz motoru sayesinde daha verimli çalışma
  - > Çapı ve ağırlığı düşürülmüş ekstra dayanıklı şanzıman
  - > LiHD teknoloji 18V 7.0Ah iki adet batarya
  - > 30 dk. tam dolduran yüksek performans şarj cihazı
  - > Çelik konstrüksiyon ve rüzgar türbinleri için ideal
- >  $\pm 5\%$  high precision torque operation
  - > Serial number and calibration certificate for each tool
  - > Four different model options from 160 - 4.000 N.m
  - > Digital display for setting and viewing Torque and Units
  - > Torque operations in N.m and Lbf.ft units
  - > More efficient operation with brushless motor
  - > Lightweight reinforced gearbox with small diameter
  - > LiHD technology 18V 7.0Ah two batteries
  - > 30 min. fully charged high-performance charger
  - > Ideal technology for wind turbines and steel construction

| Parça<br>Part | Tork Kapasitesi<br>Torque Range |          | Tork Artış<br>Torque Increment | Kare Sürücü<br>Square Drive | Şanzıman Çapı<br>Gear Diameter | Devir Hızı (d/d)<br>Idle Speed (rpm) |           | Ağırlık (kg)<br>Weight |            | Yükseklik<br>Height | Uzunluk<br>Length |
|---------------|---------------------------------|----------|--------------------------------|-----------------------------|--------------------------------|--------------------------------------|-----------|------------------------|------------|---------------------|-------------------|
| No.           | Min. N.m                        | Max. N.m | N.m                            | inch                        | (D) mm                         | @min tork                            | @max tork | Aksesuarsız            | Aksesuarlı | (A) mm              | (C) mm            |
| VT-500        | 160                             | 670      | 15                             | 3/4"                        | 65                             | 12                                   | 20        | 3,8                    | 4,7        | 265                 | 225               |
| VT-1000       | 330                             | 1.350    | 30                             | 1"                          | 72                             | 2                                    | 8         | 5,2                    | 6,6        | 265                 | 279               |
| VT-2000       | 680                             | 2.710    | 35                             | 1"                          | 78                             | 1                                    | 5         | 5,9                    | 7,2        | 265                 | 291               |
| VT-3000       | 1.020                           | 4.030    | 70                             | 1"                          | 95                             | 0,5                                  | 2         | 8,9                    | 10,2       | 265                 | 355               |

