

NSH Serisi Tek Etkili Yay Dönümlü Delikli Silindirler

NSH Series Single Acting Spring Return Hollow Cylinders



12-100 Ton



- › 700 bar maksimum çalışma basıncı
- › 12-100 ton arası hidrolik delikli silindirler
- › 40-150 mm arası stroke seçenekleri
- › Kapasitesine göre 21-81mm'ye kadar delik çapı
- › Tek etkili, yay dönüşlü standart hidrolik sistem
- › Yüksek kaliteli çatlak kontrollü 4140 çelikten imal
- › Yatay ya da ters her yönde çalışmaya uygun
- › Saplama ya da bulon çekme testi için ideal
- › Endüstriyel koşullara dayanıklı, sağlam yapı
- › Korozyona karşı dayanıklı, kaliteli boya
- › 2 yıl garantili, Türkiye'de yedek parça ve servis

- › 700 bar maximum working pressure
- › Hollow cylinders from 12 to 100 tons
- › 40-150 mm stroke options for various applications
- › 21-81 mm hollow plunger diameter options
- › Single-acting, spring-return hydraulic system
- › Manufactured from crack controlled steel
- › Suitable for working horizontally or vertically
- › Ideal for pulling and pushing applications
- › Robust construction resistant to heavy works
- › Corrosion-resistant, wear-resistant quality paint
- › 2 year warranty, parts and service in Turkey



Parça Part	Kapasite Capacity		Stroke mm	Etki Alanı Effect Area cm ²	Yağ Hacmi Oil Cap. cm ³	Ölçüler (mm) Dimensions											Ağırlık Weight kg	
	Ton	kN				A	B	C	D	E	F	H	J	K	L	P		T
NSH01204	12	121	40	18	70	124	164	21	75	55	40	19	30	3	34	18	12	3,4
NSH01208	12	121	76	18	134	176	252	21	75	55	40	19	30	3	34	18	12	4,6
NSH01215	12	121	150	18	264	300	450	21	75	55	40	19	30	3	34	18	12	7,6
NSH02205	22	217	50	32	158	165	215	27	105	75	56	23	38	3	48	20	15	8,6
NSH02208	22	217	76	32	240	203	279	27	105	75	56	23	38	3	48	20	15	11,5
NSH02215	22	217	150	32	474	318	468	27	105	75	56	23	38	3	48	20	15	16,4
NSH03005	30	302	50	44	270	197	261	34	120	90	68	27	42	4	55	22	17	12,6
NSH03006	30	302	64	44	281	197	261	34	120	90	68	27	42	4	55	22	17	13,2
NSH03015	30	302	150	44	660	322	472	34	120	90	68	27	42	4	55	22	17	18,5
NSH06008	60	578	76	84	640	223	299	56	160	125	95	25	48	4	80	22	14	29
NSH06015	60	578	153	84	1,288	315	468	56	160	125	95	25	48	4	80	22	14	38
NSH10008	100	1018	80	148	1,187	282	362	81	213	170	130	30	60	5	116	25	19	58
NSH10015	100	1018	150	148	2,225	367	517	81	213	170	130	30	60	5	166	25	19	79

