

NSX Serisi Tek Etkili Yay Dönümlü Yassı Silindirler

NSX Series Single Acting Spring Return Low Profile Cylinders

NSX Series



NETRATOOLS



- › 700 bar maksimum çalışma basıncı
- › 4-150 ton arası 700 bar hidrolik silindirler
- › 6-16 mm arası stroke seçenekleri
- › Tek etkili, yay dönüşlü standart hidrolik sistem
- › Yüksek kaliteli çatlak kontrollü 4140 çelikten imal
- › Yatay ya da ters her yönde çalışmaya uygun
- › Ekstra yassı yapısı ile dar bölgeler için ideal
- › Piston sistemi paslanmaya karşı krom kaplamalı
- › Korozyona karşı dayanıklı, aşınmaz fırın boya
- › 3 yıl garantili, Türkiye'de yedek parça ve servis

- › 700 bar maximum working pressure
- › 700 bar hydraulic cylinders from 4 to 150 tons
- › 6-16 mm stroke options for various applications
- › Single-acting, spring-return standard hydraulic system
- › Manufactured from high quality crack controlled 4140 steel
- › Suitable for working horizontally or vertically
- › Ideal for narrow areas with extra flat structure
- › Piston system is chrome-plated against rust
- › Corrosion-resistant, wear-resistant furnace paint
- › 3 year warranty, parts and service in Turkey

Parça Part	Kapasite Capacity		Stroke	Etki Alanı Effect Area	Yağ Hacmi Oil Cap.	A	B	D	E	F	O	P	S	R	Ağırlık Weight
No.	Ton	kN	mm	cm ²	cm ³	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
NSX00406	4	44	6	6	4	33	39	41	28,5	25	20	21	28	5,5	0,8
NSX00416	4	44	16	6	11	43	59	41	28,5	25	20	21	28	5,5	1,2
NSX01011	10	100	11	15	16	43	54	56	43	38	33	29	37	6,5	1,6
NSX02211	22	228	11	33	37	52	63	80	65	57	39	41	50	9	2,8
NSX03013	30	287	13	42	55	59	72	95	73	60	46	47	52	11	4,1
NSX05016	50	487	16	71	114	68	84	114	95	78	56	58	67	13	6,6
NSX07516	75	713	16	104	167	79	95	140	115	95	66	70,5	75	13	12,5
NSX10016	100	954	16	139	223	87	103	162	133	108	70	89	76	6,6	15
NSX15016	150	1450	16	211	338	100	116	194	164	134	78	108	117	9	25

