

# TU Serisi Kare Sürücülü Hidrolik Tork Anahtarları

TU Series Square Drive Hydraulic Torque Wrenches



TU Series



torcUP



- ›  $\pm 3\%$  yüksek hassasiyetli torklama imkanı
- › Her cihaz ISO17025 standartına göre kalibre edilir
- › 78.600 N.m'ye kadar hidrolik tork kuvveti
- › Patentli yekpare alüminyum gövde (Mono-Body)
- › Birbirinden bağımsız  $360^\circ \times 360^\circ$  dönebilen yağ portları
- › Sıkma ve sökme yönünde kullanıma uygun
- › İtmeli geçmeli kare sürücü ile kolay yön seçimi
- › Güvenlik kilitli, her yöne ayarlanabilir destek ayağı
- › Gövdeye işlenmiş basınç/tork ayar tablosu
- › Çok dişli tahrik sistemi ile her strokta  $27^\circ$  dönme açısı
- ›  $\pm 3\%$  high precision torque operation
- › Every unit calibrated in ISO17025 laboratory
- › Hydraulic torque capacity up to 78.600 N.m.
- › Patented Mono-Body housing
- ›  $360^\circ \times 360^\circ$  independent swivels, no drip quick connect couplers
- › Designed to tighten and loosen operations
- › Easy direction selection with Push-through square drive
- ›  $360^\circ$  adjustable reaction arm with safety lock feature
- › Laser engraved pressure/torque chart
- › Multi-Tooth drive segment allows  $27^\circ$  rotation per stroke

Parça Part	Tork Gücü (N.m) Torque Range		Sürücü Sq. Drive	Ağırlık Weight	Ölçüler (mm) Dimensions						
	Min.	Max.			inch	kg	H	L1	L2	R	W1
<b>TU-2</b>	172	1.722	3/4"	2,5	106.7	122.4	161	24.9	50.8	70.9	112.3
<b>TU-3</b>	447	4.514	1"	4,9	135.3	162.5	214.1	33.2	66.8	93.5	147.6
<b>TU-5</b>	745	7.457	1.1/2"	8,2	162.6	200.9	270.7	39.8	79.2	117.8	177.8
<b>TU-7</b>	1.003	10.031	1.1/2"	8,6	182.1	224.5	294.1	44.9	91.7	128.5	202.7
<b>TU-11</b>	1.491	14.925	1.1/2"	13,1	198.1	248.6	324.8	51.5	100.3	137.9	221.5
<b>TU-20</b>	2.630	27.964	2.1/2"	27,6	234.3	239.7	408.9	58.7	123.6	181.7	276.4
<b>TU-27</b>	3.687	36.872	2.1/2"	31,7	258.8	312.9	414.8	62.5	133.6	192.3	295.4
<b>TU-60</b>	7.862	78.625	2.1/2"	59,8	292.1	390.7	518.2	78.7	167.1	225.8	363

