


26	1	Dust Cap	TPE, black
25	1	Swivel connection	Steel, Zn 8 Silver
24	1	Sleeve	Steel, Zn-Ni 10 black
23	2	Ball	Stainless steel
22	1	Distance sleeve	Steel
21	2	Back-up ring	PTFE
20	2	Back-up ring	POM
19	1	Nut	Steel, Zn 8 silver
18	1	Locking screw	Steel, Zn 8 Silver
17	1	Swivel housing	Steel, Zn 8 silver
16	1	Locking sleeve	Hard.steel, Zn-Ni 10 black
15	9	Ball	Stainless steel
14	1	Spring	Steel
13	3	Lip seal	NBR
12	1	O-ring	NBR
11	1	O-ring	NBR
10	1	Spring housing	Steel
9	1	O-ring sleeve	Steel
8	1	Expansion sleeve	Plastic
7	1	Washer	Steel
6	1	Spring	Steel
5	1	Seal	NBR
4	1	Valve	Steel, FeZn5
3	1	O-ring	NBR
2	1	Valve seat	Steel
1	1	Front part	Steel, Zn 8 silver
Item	Qty	Description	Material

Product No. 101161250	
Nominal flow Ø DN:	2.5 mm
Connection Stroke:	18.4 mm
Max WP Connected:	1500 bar
Max WP Disconnected:	1500 bar
Min BP Connected:	3000 bar
Min BP Disconnected:	3000 bar
Temperature range:	-30°C - +100°C
Connection:	G 1/4" Fem (CMS)
Sealing material:	NBR
Hexagon:	22


 Scale: 5:2    Drawn: cabao    Checked: FR    Appr.: JE    ECO: 12067    Date: 180523  
 Drawing No. 501161250    Issue: AC    Sheet: 1/(1)

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©

