

1000 Bar Yüksek Basınç Hidrolik Kaplinler

1000 Bar High Pressure Quick Couplings

SERIES 115



- › Maksimum 1.000 bar (14.500 Psi) çalışma basıncı
- › Kaplin patlama-test basıncı 2.600 bar (37.700 Psi)
- › Dış yüzey çinko alaşımli, dayanıklı çelikten imal
- › Küçük hacimli kompakt, kullanımı ve montajı kolay
- › Hızlı geçmeli sistem, montajda el aleti gerektirmez
- › Bağlantıda ve ayırmada sızdırma-damlatma yapmaz
- › Tüm kaplinlerde kilit mekanizması ile maksimum güvenlik

- › Maximum working pressure 1.000 bar (14.500 Psi)
- › Coupling burst pressure 2.600 bar (37.700 Psi)
- › Outer surface is zinc plated, made of durable steel
- › Compact design, easy to use and assemble
- › Quick connect system, no need for hand tools in installation
- › Non-drip couplings with clean connection and disconnection
- › Maximum security with safety lock on all couplings

İçten Dış Kaplin Gövdeleri

Female Threaded Couplings



Model No.	Bağlantı Connection	Uzunluk Length	Çap Ø Diameter	Montaj Torqu Req. Torque
#	#	mm	mm	N.m
10 115 1202	G 1/4"	61,3	28	40-50
10 115 1402	1/4" NPT	60,4	28	50-60
10 115 1404	3/8" NPT	60,4	28	70-80
10 115 1401	1/8" NPT	60,4	28	40-50
10 115 1102	Rc 1/4"	60,4	28	50-60
10 115 1104	Rc 3/8"	60,8	28	70-80
10 115 1201	G 1/8"	60,4	28	40-50
10 115 1204	G 3/8"	63,3	28	70-80

İçten Dış Kaplin Uçları

Female Threaded Nipples



Model No.	Bağlantı Connection	Uzunluk Length	Çap Ø Diameter	Montaj Torqu Req. Torque
#	#	mm	mm	N.m
10 115 6102	Rc 1/4"	36,7	24,7	30-40
10 115 6104	Rc 3/8"	38	27,7	40-50
10 115 6201	G 1/8"	33,3	19,6	40-50
10 115 6202	G 1/4"	38	24,7	40-50
10 115 6204	G 3/8"	39,5	26,7	70-80
10 115 6401	1/8" NPT	33,3	19,6	20-25
10 115 6402	1/4" NPT	35,7	25,4	30-40
10 115 6404	3/8" NPT	37	27,7	40-50

Dıştan Dış Kaplin Gövdeleri

Male Threaded Couplings



Model No.	Bağlantı Connection	Uzunluk Length	Çap Ø Diameter	Montaj Torqu Req. Torque
#	#	mm	mm	N.m
10 115 1252	G 1/4"	71,8	28	40-50
10 115 1254	G 3/8"	71,8	28	70-80
10 115 1452	1/4" NPT	72,3	28	50-60
10 115 1454	3/8" NPT	72,8	28	70-80

Dıştan Dış Kaplin Uçları

Male Threaded Nipples



Model No.	Bağlantı Connection	Uzunluk Length	Çap Ø Diameter	Montaj Torqu Req. Torque
#	#	mm	mm	N.m
10 115 6152	R 1/4"	63	25,4	50-60
10 115 6154	R 3/8"	63	25,4	70-80
10 115 6212	G 1/4"	50,3	24,7	40-50
10 115 6254	G 3/8"	62	25,4	70-80
10 115 6451	1/8" NPT	50,8	19,6	40-50
10 115 6452	1/4" NPT	61,5	25,4	50-60
10 115 6454	3/8" NPT	62	25,4	70-80
10 115 6272	G 1/4"	52	24,7	40-50



Kullanım Alanları:

- Saplama Gerdirmeler
- Test Tezgahları
- Silindirler
- Çektirmeler
- Tork Aletleri
- Arama-Kurtarma Ekipmanları

Application Areas:

- Bolt Tensioners
- Test Benches
- Cylinders
- Bearing Pullers
- Torque Tools
- Rescue Tools