

7440 Serisi Kraftform Torklu Tornavida Setleri

7440 Series Kraftform Torque Screwdriver Sets



0,1 - 3,0 N.m



- TS EN ISO 6789 standartına uygun $\pm 6\%$ hassasiyet
 - Seri numaralı izlenebilir tork kalibrasyon sertifikası
 - Küçük ölçekli, okunaklı lazer işlemeli tork ayar skalası
 - Rapidaptor 1/4" bits tutucu ile hızlı uç değişimi
 - Set içeriğinde 24 adet değiştirilebilir bits uç bulunur
 - Clutch mekanizma ile ayarlanan torkun üzerinde sıkılmaz
 - Ayarlanan torka erişince debriyaj sistemi boşa çıkar
 - Wera tork tornavidaları sökme yönünde tork uygulamaz
 - Sökme yönünde standart tornavida gibi kullanılabilir
-
- Accuracy $\pm 6\%$ according to TS EN ISO 6789
 - Traceable torque calibration document with serial number
 - Small scale, legible laser engraved torque setting scale
 - Rapidaptor technology for rapid bit change
 - Set includes 24 bits and adjustable torque screwdrivers
 - Clutch mechanism prevents over torquing
 - Wera torque screwdrivers can't apply torque in CCW direction
 - Can be used as a standard screwdriver in CCW direction

| Model Adı Model Name | Parça Part | Tork Kapasitesi Torque Capacity |
|-------------------------|---------------|--|
| # | No. | N.m |
| 7440/41 | 05074738001 | 1 x 0.3-1.2 (7440) 1 x 1.2-3.0 (7441) |
| 7440/41/42 | 05074739001 | 1 x 0.3-1.2 (7440) 1 x 1.2-3.0 (7441) 1 x 3.0-6.0 (7442) |

7440/41



7440/41/42



| 867/1 TZ TORX® | 867/1 IP TORX PLUS® | 840/1 Z HEX-PLUS |
|-------------------|------------------------|---------------------|
| | | |
| 1 x TX 6x25 | 1 x 6 IPx25 | 1 x 2.0x25 |
| 1 x TX 7x25 | 1 x 7 IPx25 | 1 x 2.5x25 |
| 1 x TX 8x25 | 1 x 8 IPx25 | 1 x 3.0x25 |
| 1 x TX 9x25 | 1 x 9 IPx25 | 1 x 4.0x25 |
| 1 x TX 10x25 | 1 x 10 IPx25 | 1 x 5.0x25 |
| 1 x TX 15x25 | 1 x 15 IPx25 | 1 x 6.0x25 |
| 1 x TX 20x25 | 1 x 20 IPx25 | |
| 1 x TX 25x25 | 1 x 25 IPx25 | |
| 1 x TX 30x25 | 1 x 30 IPx25 | |

