

700 Bar Hidropnömatik Ayak Pompaları

700 Bar Hydropneumatic Pumps

AP Series



POWERRAM
HYDRAULIC TOOLS



AP921

- 700 bar maksimum çalışma basıncı
- Tek etkili ve çift etkili havalı ayak pompaları
- Dahili emniyet valfi maksimum iş güvenliği sağlar
- 7-10 bar hava basıncı ile 700 bar hidrolik güç
- Şase doğrultma uygulamaları için ideal ve ekonomik
- Alüminyumdan imal, ağır çalışma şartlarına dayanıklı
- Hafif yapısı sayesinde portatif kullanım imkanı
- Manometre opsiyonel olarak sunulur (Ø100 – Ø63 mm)
- 2 yıl garantili, Powerram marka, menşei Taiwan

Opsiyonel Aksesuarlar / Optional Accessories

Hortumlar
Hoses



Kaplinler
Quick Couplings



Dijital Manometre
Digital Gauge



- 700 bar maximum working pressure
- Single and double acting hydropneumatic pumps
- Built-in safety valve ensures maximum safety
- 700 bar hydraulic power with 7-10 bar air pressure
- Ideal for chassis straightening applications and economical
- Made of aluminum, suitable for heavy duty applications
- Lightweight and easy to carry compact design
- Ø63 mm analog gauge is available as an option
- 2 year warranty, POWERRAM brand, origin Taiwan

Parça Part	Çalışma Basıncı Working Pressure	Tank Kapasitesi Oil Capacity	Kullanılabilir Yağ Effective Oil	Hava Basıncı Air Pressure	Yağ Debisi (cm ³) Oil Flow		Bağlantı Dış Ölçüsü Connection Ports	
					@70 Bar	@700 Bar	Hortum Hose	Manometre Gauge
No.	Bar	Litre	Litre	Bar				
AP921	700	0,85	0,75	7-10	700	100	1/4" NPT	1/4" NPT
AP922	700	0,85	0,75	7-10	700	100	3/8" NPT	1/4" NPT
AP1600S	700	1,60	1,3	7-10	1250	193	3/8" NPT	1/4" NPT
AP3000S	700	3,0	2,5	7-10	1250	193	3/8" NPT	1/4" NPT
AP1600D*	700	1,60	1,3	7-10	1250	193	3/8" NPT	1/4" NPT
AP3000D*	700	3,0	2,5	7-10	1250	193	3/8" NPT	1/4" NPT

* Çift etkili modeller / Double acting models

Parça Part	Ölçüler (mm) Dimensions							Ağırlık Weight
	A	B	C	D	E	F	G	
No.								kg
AP921	423	170	70	399	160	47	59	5,4
AP922	423	170	70	399	160	47	59	5,4
AP1600S	242	129	90	257	150,4	112,6	205	7,3
AP3000S	309	160	90	325	151,3	113,5	205	9,3
AP1600D*	242	129	98	304	188	112,6	245	9,1
AP3000D*	309	160	98	343	189	113,5	246	12

