



Oynar başlık opsiyoneldir
Tilting saddle is optional



- › 50-1.100 tona kadar kilit somunlu silindirler
- › Farklı işlere uygun 45-50 mm stroke seçeneği
- › Yassı tip tasarımı sayesinde dar alanlara uygun
- › Tek etkili, yük dönüşlü standart hidrolik sistem
- › Stroke aşım valfi ile üst düzey iş güvenliği
- › Vidalı piston ile uzun süre yük altında bekleme
- › Endüstriyel ağır işlere dayanıklı sağlam yapı
- › 2 yıl garantili, Türkiye'de yedek parça ve servis
- › Lock-nut hydraulic cylinders from 50 to 1.100 tons
- › 45-50 mm stroke options for various applications
- › Suitable for narrow and hard-to-work areas
- › Single-acting, load-return standard hydraulic system
- › Hydraulic "end of stroke" overflow port for security
- › Lock nut (screw piston) holds the load mechanically
- › Robust construction resistant to heavy industrial work
- › 2 year warranty, spare parts and service in Turkey

Tamamlayıcı Ekipmanlar / Complementary Equipment

El Pompaları / Hand Pumps

Güç Üniteleri / Power Packs

700 Bar Hortumlar / Hoses

Manometreler / Gauges

Kaplinler / Quick Couplings



Parça Part	Kapasite Capacity		Stroke	Etki Alanı Effect Area	Yağ Hacmi Oil Cap.	Ölçüler (mm) Dimensions						Ağırlık Weight	
No.	Ton	kN	mm	cm ²	cm ³	A	B	D	E	H	J	L	kg
NLX05005	50	486	50	71	355	125	175	120	95	19	21	92	11
NLX09004	90	911	45	133	597	137	182	165	130	21	31	126	22
NLX12002	120	1.185	25	176	250	125	150	198	150	25	30	126	30
NLX14004	140	1.380	45	201	905	148	193	200	160	27	38	148	39
NLX22004	220	2.156	45	314	1413	155	200	255	200	28	40	157	62
NLX35004	350	3.468	45	491	2208	178	223	310	250	35	50	240	111
NLX43004	430	4.227	45	616	2771	184	229	340	280	35	55	260	126
NLX56004	550	5.520	45	804	3618	192	237	390	320	38	60	295	193
NLX67004	670	6.600	45	962	4330	236	281	430	350	50	75	295	259
NLX88004	880	8.620	45	1257	5655	268	313	490	400	60	85	325	482
NLX110004	1.100	10.905	45	1590	7157	295	340	550	450	65	95	400	532

