



## Değişken Uçlu Tork Anahtarı Setleri

Interchangeable Torque Wrench Sets

**TW060-29P / TW200-28P**



- › TS EN ISO 6789 standardına uygun  $\pm 3\%$  hassasiyet
  - › 10 – 60 N.m ve 40 – 200 N.m kapasitede iki set
  - › 9x12 ve 14x18mm girişli açık ağız, kapalı yıldız uçlar
  - › Her iki sette cırcır uç da vardır (3/8" – 1/2")
  - › Tork anahtarları dikdörtgen girişli tüm uçlara uyumludur
  - › Hassas ve okunaklı mikrometre tip tork ayar skalası
  - › Seri numaralı izlenebilir tork kalibrasyon sertifikası
  - › DIN ISO 6789 & ASME B107.300-2010 kalite standardı
  - › Türkiye'de servis, yedek parça ve kalibrasyon imkânı
- 
- › Accuracy  $\pm 3\%$  according to TS EN ISO 6789
  - › Two sets of 10 - 60 N.m and 40 - 200 N.m capacity
  - › 9x12 and 14x18mm open end, ring end & open ring inserts
  - › Including ratchet square drive for socket use (3/8" & 1/2")
  - › Compatible with all inserts with rectangular input
  - › Precise, easy-to-read micrometer type torque setting scale
  - › Ergonomic shape with non-slip handle design
  - › DIN ISO 6789 & ASME B107.300-2010 quality standard
  - › Traceable calibration certificate for the clockwise direction

Model No.	Tork Kapasitesi Torque Range		Uç Giriş Ölçüsü Insert Tool	Cırcır Uç Ratchet Type	Açık Ağız Open End	Kapalı Yıldız Ring End	Açık Yıldız Open Ring	Ağırlık Weight
	#	N.m						
TW060-29P	10 - 60	9 - 42	9x12	3/8"	7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17	7, 8, 10, 11, 12, 13, 14, 15, 16, 17	10, 11, 12, 13, 14, 17	4,25
TW200-28P	40 - 200	33 - 143	14x18	1/2"	13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32	13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32	-	5,75

