

Cırcır Mekanizmalı Endüstriyel Tork Anahtarları

Industrial Torque Wrenches with Ratchet Mechanism



CTR



- > TS EN ISO 6789 standardına uygun $\pm 3\%$ hassasiyet
- > 2 – 600 N.m kapasitede farklı tork anahtarları
- > Endüstriyel uygulamalara uygun sağlam yapı
- > Sıkma – sökme işlerini kolaylaştıran mandallı cırcır
- > Yön seçimi cırcır üzerindeki mandal ile yapılır
- > Hızlı lokma değişimi sağlayan cırcır mekanizması
- > Gövdeye işlemeli hasas ve okunaklı tork ayar skalası
- > Seri numaralı izlenebilir tork kalibrasyon sertifikası
- > DIN ISO 6789 & ASME B107.300-2010 kalite standardı
- > Türkiye’de servis, yedek parça ve servis imkânı

- > Accuracy $\pm 3\%$ according to TS EN ISO 6789
- > Different torque wrenches in the range of 2 to 600 N.m
- > Suitable for heavy duty industrial applications
- > Robust ratchet mechanism for CW and CCW directions
- > Direction selection is applied from top of the ratchet
- > Ratchet mechanism providing rapid socket change
- > Precise, easy-to-read torque setting scale on the body
- > Ergonomic shape with non-slip knurled handle design
- > DIN ISO 6789 & ASME B107.300-2010 quality standard
- > Traceable calibration certificate for the clockwise direction



Model No.	Tork Kapasitesi Torque Range		Kare Sürücü Square Drive	Cırcır Dış Ratchet Teeth	Ölçek Increment	Uzunluk Length	Ağırlık Weight
#	N.m	Lb.ft - Lb.in	inch	#	N.m	mm	kg
CTR-010P*	2,0 - 10	22 - 84	1/4"	24T	0,1	281	0,60
CTR-020P*	4,0 - 20	40 - 172	1/4"	24T	0,1	329	0,65
CTR-060	10 - 60	9,2 - 42,4	3/8"	32T	0,5	370	0,84
CTR-100A	20 - 100	16,6 - 71,9	3/8"	32T	0,5	433	1,0
CTR-100B	20 - 100	16,6 - 71,9	1/2"	32T	0,5	433	1,0
CTR-200	40 - 200	33 - 144	1/2"	32T	1,0	530	1,65
CTR-350	50 - 350	44 - 251	1/2"	32T	2,0	610	1,8
CTR-400	80 - 400	66 - 288	1/2"	32T	2,0	610	1,8
CTR-420	60 - 420	52 - 302	1/2"	32T	2,0	610	1,8
CTR-600	100 - 600	92 - 424	3/4"	24T	5,0	1050	5,3

* İşaretili modeller plastik tutma koluna sahiptir. / *Marked models have plastic handle.

