



Pencereli Tip Sürgülü Cırcırlı Tork Anahtarları

NovaTork®

Window Scaled Torque Wrenches with Push-Through Ratchet Head

STMX



- › TS EN ISO 6789 standardına uygun $\pm 4\%$ hassasiyet
- › 5 – 1500 N.m kapasitede farklı tork anahtarları
- › Sıkma – sökme yönünde çalışan geçmeli tip cırcır
- › Hassas ve okunaklı pencereli tip ikili tork ayar skalası
- › Kaymaz, ergonomik ve sağlam plastik tutma kolu
- › Standarttan uzun yapısıyla daha rahat kullanılır
- › Seri numaralı izlenebilir tork kalibrasyon sertifikası
- › Türkiye’de servis, yedek parça ve kalibrasyon imkânı
- › Accuracy $\pm 4\%$ according to TS EN ISO 6789
- › Different torque wrenches in the range of 5 to 1500 N.m
- › Push-Through ratchet head for CW and CCW directions
- › Easy-to-read window type dual scale with fine increments
- › Ergonomic, durable, non-slip plastic handle
- › Longer than standards, more efficiently, easy to use
- › Push/Pull end cap to secure the set torque value
- › Traceable calibration certificate for the clockwise direction

Model No.	Tork Kapasitesi Torque Range		Kare Sürücü Square Drive	Ölçek Increment	Cırcır Genişliği Ratchet Width	Uzunluk Length	Ağırlık Weight
	#	N.m					
STMX125	5,0 - 25	4,0 - 20	1/4"	0,20	27	328	0,84
STMX260	10 - 60	9,0 - 45	3/8"	0,50	37	392	1,00
STMX3100	20 - 100	15 - 75	1/2"	0,50	45	434	1,10
STMX3150	30 - 150	25 - 115	1/2"	1,00	45	496	1,25
STMX3200	40 - 200	30 - 150	1/2"	1,00	45	496	1,25
STMX3300	60 - 300	45 - 225	1/2"	1,50	45	556	1,40
STMX3400	80 - 400	60 - 300	1/2"	2,00	50	700	1,97
STMX4550	100 - 550	80 - 405	3/4"	3,00	70	889	3,67
STMX4750	150 - 750	110 - 550	3/4"	5,00	70	1110	4,10
STMX41000	200 - 1000	150 - 750	3/4"	5,00	70	1210	4,67
STMX51500	300 - 1500	200 - 1100	1"	10,00	90	1710	6,50

