

# Pencereli Tip Değişken Uçlu Tork Anahtarları

Window Scaled Interchangeable Torque Wrenches

STMH

NovaTork®



- > TS EN ISO 6789 standardına uygun  $\pm 4\%$  hassasiyet
  - > 5 – 550 N.m arası kapasitede farklı tork anahtarları
  - > 9x12 ve 14x18 mm dikdörtgen girişli uçlarla uyumludur
  - > Hassas ve okunaklı pencereli tip ikili tork ayar skalası
  - > Kaymaz, ergonomik ve sağlam plastik tutma kolu
  - > Standarttan uzun yapısıyla daha rahat kullanılır
  - > Seri numaralı izlenebilir tork kalibrasyon sertifikası
  - > Türkiye’de servis, yedek parça ve kalibrasyon imkânı
- > Accuracy  $\pm 4\%$  according to TS EN ISO 6789
  - > Different torque wrenches in the range of 5 to 550 N.m
  - > Compatible with 9x12 & 14x18 mm rectangular inserts
  - > Easy-to-read window type dual scale with fine increments
  - > Ergonomic, durable, non-slip plastic handle
  - > Longer than standards, more efficiently, easy to use
  - > Push/Pull end cap to secure the set torque value
  - > Traceable calibration certificate for the clockwise direction

Model No.	Tork Kapasitesi Torque Range		Uç Giriş Ölçüsü Insert Tool	Ölçek Increment	Genişlik Width	Uzunluk Length	Ağırlık Weight
	#	N.m					
STMH925	5,0 - 25	4,0 - 20	9x12	0,20	24	315	0,70
STMH960	10 - 60	9,0 - 45	9x12	0,50	24	376	0,82
STMH9100	20 - 100	15 - 75	9x12	0,50	24	376	0,82
STMH14150	30 - 150	25 - 115	14x18	1,00	32	466	1,15
STMH14200	40 - 200	30 - 150	14x18	1,00	32	484	1,20
STMH14300	60 - 300	45 - 225	14x18	1,50	32	544	1,20
STMH14400	80 - 400	60 - 300	14x18	2,00	32	700	1,60
STMH14550	100 - 550	80 - 405	14x18	2,50	32	875	2,00

